

# SAFETY DATA SHEET

## Klean-Strip Fiberglass Paint Remover

Page: 1

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/25/2015

### 1. PRODUCT AND COMPANY IDENTIFICATION

|                               |   |                                       |
|-------------------------------|---|---------------------------------------|
| <b>Product Name:</b>          | Klean-Strip Fiberglass Paint Remover  |                                       |
| <b>Company Name:</b>          | W. M. Barr<br>2105 Channel Avenue<br>Memphis, TN 38113  | <b>Phone Number:</b><br>(901)775-0100 |
| <b>Web site address:</b>      | www.wmbarr.com  |                                       |
| <b>Emergency Contact:</b>     | 3E 24 Hour Emergency Contact  | (800)451-8346                         |
| <b>Information:</b>           | W.M. Barr Customer Service  | (800)398-3892                         |
| <b>Intended Use:</b>          | Paint/Varnish Remover   |                                       |
| <b>Synonyms:</b>              | GAF354  |                                       |
| <b>Additional Information</b> | This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product. |                                       |

### 2. HAZARDS IDENTIFICATION

**Flammable Liquids, Category 2**  
**Acute Toxicity: Oral, Category 4**  
**Acute Toxicity: Skin, Category 4**  
**Acute Toxicity: Inhalation, Category 4**  
**Skin Corrosion/Irritation, Category 1A-1C**  
**Serious Eye Damage/Eye Irritation, Category 2A**  
**Carcinogenicity, Category 1B**  
**Toxic To Reproduction, Category 2**  
**Specific Target Organ Toxicity (single exposure), Category 1**  
**Specific Target Organ Toxicity (repeated exposure), Category 2**



|                                |  |
|--------------------------------|--|
| <b>GHS Signal Word:</b>        | <b>Danger</b>  |
| <b>GHS Hazard Phrases:</b>     | H225: Highly flammable liquid and vapor.<br>H302: Harmful if swallowed.<br>H312: Harmful in contact with skin.<br>H314: Causes severe skin burns and eye damage.<br>H319: Causes serious eye irritation.<br>H332: Harmful if inhaled.<br>H350: May cause cancer.<br>H361: Suspected of damaging fertility or the unborn child.<br>H370: Causes damage to organs.<br>H373: May cause damage to organs through prolonged or repeated exposure.                                     |
| <b>GHS Precaution Phrases:</b> | P201: Obtain special instructions before use.<br>P202: Do not handle until all safety precautions have been read and understood.<br>P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.<br>P233: Keep container tightly closed.<br>P241: Use explosion-proof electrical/ventilating/lighting equipment.<br>P242: Use only non-sparking tools.<br>P243: Take precautionary measures against static discharge.<br>P260: Do not breathe gas/mist/vapors/spray. |

# SAFETY DATA SHEET

## Klean-Strip Fiberglass Paint Remover

**GHS Response Phrases:**


P264: Wash hands thoroughly after handling.  
P270: Do not eat, drink or smoke when using this product.  
P271: Use only outdoors or in a well-ventilated area.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P281: Use personal protective equipment as required.  
P301+312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.  
P302+352: IF ON SKIN: Wash with plenty of soap and water.  
P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P307+311: IF exposed: Call a POISON CENTER or doctor/physician.  
P308+313: IF exposed or concerned: Get medical attention/advice.  
P310: Immediately call a POISON CENTER or doctor/physician.  
P314: Get medical attention/advice if you feel unwell.  
P321: Specific treatment see label.  
P330: Rinse mouth.  
P337+313: If eye irritation persists, get medical advice/attention.  
P363: Wash contaminated clothing before reuse.

**GHS Storage and Disposal Phrases:**

P403+235: Store in cool/well-ventilated place.  
P405: Store locked up.  
P501: Dispose of contents/container according to local, state and federal regulations.

**Hazard Rating System:**

|              |   |   |
|--------------|---|---|
| HEALTH       | * | 3 |
| FLAMMABILITY |   | 2 |
| PHYSICAL     |   | 0 |
| PPE          |   | D |

**HMIS:****OSHA Regulatory Status:**

This material is classified as hazardous under OSHA regulations.

**Potential Health Effects (Acute and Chronic):****INHALATION ACUTE EFFECTS:**

Vapor harmful. May cause dizziness; headache; watering of eyes; irritation of respiratory tract; nausea; numbness in fingers, arms, and legs; hot flashes; loss of appetite; spotted vision; fatigue; dilation of pupils; increase of carboxyhemoglobin levels, which can cause stress to the cardiovascular system; arm, leg and chest pains; depression of the central nervous system; visual disturbances; giddiness and intoxication; sleepiness; cough and dyspnea; cold, clammy extremities; diarrhea; vomiting; and hallucinations. Severe overexposure may cause irregular or rapid heartbeat; convulsions; unconsciousness; coma; and death. Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal. Elevated carboxyhemoglobin levels can be additive to the increase caused by smoking and other carbon monoxide sources.

**SKIN CONTACT ACUTE EFFECTS:**

This product is a skin irritant. May be absorbed through the skin. May cause irritation; drying of skin; numbness in fingers and arms; defatting of skin; and dermatitis. May cause symptoms listed under inhalation.

**EYE CONTACT ACUTE EFFECTS:**

This material is an eye irritant. May cause irritation; burns; conjunctivitis of eyes; and corneal ulcerations of the eye. Vapors may irritate eyes.

# SAFETY DATA SHEET

## Klean-Strip Fiberglass Paint Remover

Page: 3

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/25/2015

### INGESTION ACUTE EFFECTS:

POISON. CANNOT BE MADE NON-POISONOUS. May be fatal or cause blindness. May cause dizziness; headache; nausea; vomiting; loss of coordination; stupor; irritation in mouth, throat and stomach; burning sensation in mouth, throat and stomach; gastrointestinal irritation; diarrhea; loss of appetite; depression of the central nervous system; narcosis; liver, kidney and heart damage; coma; and death. May produce symptoms listed under inhalation. Liquid aspirated into lungs, during vomiting, may cause chemical pneumonia and systemic effects.

### CHRONIC EFFECTS:

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Prolonged or repeated contact may cause dermatitis. Prolonged skin contact may result in absorption of a harmful amount of this material. May cause conjunctivitis; gastric disturbances; insomnia; giddiness; dizziness; headache; weakness; fatigue; nausea; skin irritation; numbness in hands and feet; pancreatic damage; permanent central nervous system changes; decreased response to visual and auditory stimulation; some loss of memory; visual impairment or blindness; hallucinations; changes in blood; blood disorders; kidney and liver damage; heart palpitations; and death. May cause additional symptoms listed under inhalation.

### PRIMARY ROUTES OF EXPOSURE:

Inhalation, ingestion, and dermal.

### TARGET ORGANS:

Central nervous system, skin, kidney, liver, blood, lungs, respiratory system, and eyes

**Medical Conditions Generally Aggravated By Exposure:** Diseases of the blood, skin, eyes, liver, kidneys, lungs, cardiovascular system and respiratory system; alcoholism; and rhythm disorders of the heart.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

| CAS #    | Hazardous Components (Chemical Name)                 | Concentration | RTECS #   |
|----------|--|---------------|-----------|
| 108-88-3 | Toluene {Benzene, Methyl-, Toluol}                   | 15.0 -40.0 %  | XS5250000 |
| 75-09-2  | Dichloromethane {Methylene chloride; R-30; Freon 30} | 10.0 -30.0 %  | PA8050000 |
| 67-64-1  | Acetone {2-Propanone}                                | 10.0 -30.0 %  | AL3150000 |
| 67-56-1  | Methanol {Methyl alcohol; Carbinol; Wood alcohol}    | 10.0 -20.0 %  | PC1400000 |

**Additional Chemical Information** Specific percentage of composition is being withheld as a trade secret.

## 4. FIRST AID MEASURES

|  |  |
|--|--|
| <b>Emergency and First Aid Procedures:</b> | <b>INHALATION</b><br>If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.   |
|  | <b>SKIN CONTACT</b><br>Immediately wash with soap and large quantities of water. Seek medical attention if irritation from contact persists.   |
|  | <b>EYE CONTACT</b><br>Flush with large quantities of water, remove any contact lens, and continue flushing with water for at least 15 minutes, then seek immediate medical attention.  |
|  | <b>INGESTION</b><br>Call your poison control center, hospital emergency room or physician immediately for instructions to induce vomiting.   |
| <b>Signs and Symptoms Of Exposure:</b>     | See Potential Health Effects.  |
| <b>Note to Physician:</b>                  | <b>POISON. THIS PRODUCT CONTAINS METHANOL AND METHYLENE CHLORIDE.</b><br><br>This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis. |

## 5. FIRE FIGHTING MEASURES

|  |  |
|--|--|
| <b>Flash Pt:</b>                         | NFPA Class 1B<br>10.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)   |
| <b>Explosive Limits:</b>                 | LEL: 1.2 % UEL: 36 %   |
| <b>Autoignition Pt:</b>                  | No data.   |
| <b>Suitable Extinguishing Media:</b>     | Carbon dioxide, dry powder or alcohol resistant foam. Water spray may be used, but may be ineffective at extinguishing the fire.   |
| <b>Unsuitable Extinguishing Media:</b>   | None known.  |
| <b>Fire Fighting Instructions:</b>       | Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.  |
| <b>Flammable Properties and Hazards:</b> | <b>DANGER! FLAMMABLE. KEEP AWAY FROM HEAT, SPARKS, FLAME AND ALL OTHER SOURCES OF IGNITION. VAPORS MAY CAUSE FLASH FIRE OR IGNITE EXPLOSIVELY. VAPORS MAY TRAVEL LONG DISTANCES TO OTHER AREAS AND ROOMS AWAY FROM WORK SITE.</b> Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition anywhere in the structure, dwelling or building during use and until all vapors are gone from the work site and all areas away from the work site. Keep away from electrical outlets and switches. Beware of static electricity that may be generated by synthetic clothing and other sources. |

# SAFETY DATA SHEET

## Klean-Strip Fiberglass Paint Remover

Page: 5  
Printed: 04/17/2015  
Revision: 04/17/2015  
Supersedes Revision: 03/25/2015

Flammability Classification:

### 6. ACCIDENTAL RELEASE MEASURES

**Steps To Be Taken In Case Material Is Released Or Spilled:** Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding procedures. Keep material out of waterways, bodies of water, and sewers.

**SMALL SPILLS:** Take up liquid with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

**LARGE SPILLS:** Dike far ahead of spill. If possible collect material for reuse. Collect remainder of material for proper disposal.

### 7. HANDLING AND STORAGE

**Precautions To Be Taken in Handling:** Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Avoid breathing of vapors or mist and contact with skin, eyes, and clothing.

A source of clean water should be immediately available for flushing of the eyes and skin should contact occur.

**Precautions To Be Taken in Storing:** Store in a cool, dry place. Keep container tightly closed. Exposure to high temperatures or prolonged exposure to sun may cause can to leak or swell. Once opened, remover should be used within six months or discarded to avoid can deterioration. Do not store near flames or at elevated temperatures.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

| CAS #    | Partial Chemical Name                                | OSHA TWA   | ACGIH TWA                     | Other Limits |
|----------|--|--|-------------------------------|--------------|
| 108-88-3 | Toluene {Benzene, Methyl-; Toluol}                   | PEL: 200 ppm<br>STEL: 500 ppm/(10min)<br>CEIL: 300 ppm | TLV: 50 ppm                   | No data.     |
| 75-09-2  | Dichloromethane {Methylene chloride; R-30; Freon 30} | PEL: 25 ppm<br>STEL: 125 ppm (15 min)                  | TLV: 50 ppm                   | No data.     |
| 67-64-1  | Acetone {2-Propanone}                                | PEL: 1000 ppm  | TLV: 500 ppm<br>STEL: 750 ppm | No data.     |
| 67-56-1  | Methanol {Methyl alcohol; Carbinol; Wood alcohol}    | PEL: 200 ppm   | TLV: 200 ppm<br>STEL: 250 ppm | No data.     |

**Respiratory Equipment (Specify Type):** For OSHA controlled work place and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved supplied air respirator or breathing apparatus for chlorinated solvent vapors. A dust mask does not provide protection against vapors.

**Eye Protection:** Safety glasses, chemical goggles, or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Chemical goggles or face shields are

# SAFETY DATA SHEET

## Klean-Strip Fiberglass Paint Remover

Page: 6  
Printed: 04/17/2015  
Revision: 04/17/2015  
Supersedes Revision: 03/25/2015

|   |   |
|---|---|
| <b>Protective Gloves:</b>                       | recommended when splashing or spraying of chemical is possible. A faceshield provides more protection to help reduce chemical contact to the face and eyes.<br>Wear gloves with as much resistance to the chemical ingredients as possible. Laminate film gloves offer the best protection. Other glove materials, such as nitrile rubber, will be degraded by methylene chloride, but may provide protection for some amount of time, based on the type of glove and the conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.               |
| <b>Other Protective Clothing:</b>               | Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.  |
| <b>Engineering Controls (Ventilation etc.):</b> | Use only with adequate ventilation to prevent build up of vapors. Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms, and small enclosed areas. Whenever possible, use outdoors in an open air area. If strong odor is noticed or you experience slight dizziness - STOP - ventilation is not adequate. Leave area immediately. If the work area is not adequately ventilated, do not use this product.<br><br>For OSHA controlled workplaces, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. |
| <b>Work/Hygienic/Maintenance Practices:</b>     | Wash hands thoroughly after use and before eating, drinking, or smoking.<br>Do not eat, drink, or smoke in the work area.<br><br>Discard any clothing or other protective equipment that cannot be decontaminated.<br><br>Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.  |

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|   |   |
|---|---|
| <b>Physical States:</b>                   | [ ] Gas [ X ] Liquid [ ] Solid                              |
| <b>Appearance and Odor:</b>               | Solvent odor.   |
| <b>Melting Point:</b>                     | No data.  |
| <b>Boiling Point:</b>                     | 104.00 F - 230.00 F   |
| <b>Autoignition Pt:</b>                   | No data.  |
| <b>Flash Pt:</b>                          | 10.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash) |
| <b>Explosive Limits:</b>                  | LEL: 1.2 % UEL: 36 %  |
| <b>Specific Gravity (Water = 1):</b>      | No data.  |
| <b>Density:</b>                           | 7.451 LB/GL at 77.0 F                                       |
| <b>Vapor Pressure (vs. Air or mm Hg):</b> | 40 mm Hg - (of VOC) at 68.0 F                               |
| <b>Vapor Density (vs. Air = 1):</b>       | > 1   |
| <b>Evaporation Rate:</b>                  | > 1   |
| <b>Solubility in Water:</b>               | Partially   |
| <b>Percent Volatile:</b>                  | 98.0 % by weight.   |
| <b>VOC / Volume:</b>                      | 49.1000 % WT  |

**SAFETY DATA SHEET**  
**Klean-Strip Fiberglass Paint Remover**

Page: 7  
Printed: 04/17/2015  
Revision: 04/17/2015  
Supersedes Revision: 03/25/2015

**10. STABILITY AND REACTIVITY**

|   |  |
|---|--|
| <b>Stability:</b>                                 | Unstable [ <input type="checkbox"/> ]    Stable [ <input checked="" type="checkbox"/> ]  |
| <b>Conditions To Avoid - Instability:</b>         | No data available.   |
| <b>Incompatibility - Materials To Avoid:</b>      | Incompatible with strong oxidizing agents; strong caustics; strong alkalis; oxygen; nitrogen peroxide; chemically active metals such as aluminum or magnesium; sodium; potassium; and nitric acid. |
| <b>Hazardous Decomposition Or Byproducts:</b>     | Thermal decomposition may produce hydrogen chloride; chlorine gas; small quantities of phosgene; carbon monoxide; carbon dioxide; formaldehyde; and unidentified organic compounds in black smoke. |
| <b>Possibility of Hazardous Reactions:</b>        | Will occur [ <input type="checkbox"/> ]    Will not occur [ <input checked="" type="checkbox"/> ]  |
| <b>Conditions To Avoid - Hazardous Reactions:</b> | No data available.   |

**11. TOXICOLOGICAL INFORMATION**

|                                   |  |
|-----------------------------------|--|
| <b>Toxicological Information:</b> | <p>This product has not been tested as a whole. Refer to section 2 for acute and chronic effects.</p> <p>CAS# 108-88-3:<br/>Reproductive Effects:, TClO, Inhalation, Rat, 800.0 MG/M3, 6 H, female 14-20 day(s) after conception.<br/>Result:<br/>Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).<br/>Effects on Newborn: Behavioral.<br/>- Brazilian Journal of Medical and Biological Research., Vol/p/yr: 23,533, 1990</p> <p>Standard Draize Test, Eyes, Species: Rabbit, 2.000 MG, 24 H, Severe.<br/>Result:<br/>Effects on Embryo or Fetus: Other effects to embryo.<br/>Specific Developmental Abnormalities: Eye, ear.<br/>- Prehled Prumyslove Toxikologie, Marhold, J., Organicke Latky, Prague Czechoslovakia, Vol/p/yr: -,29, 1986</p> <p>CAS# 75-09-2:<br/>Tumorigenic Effects:, TClO, Inhalation, Rat, 3500. PPM, 6 Y.<br/>Result:<br/>Tumorigenic: Carcinogenic by RTECS criteria.<br/>Endocrine: Tumors.<br/>- Fundamental and Applied Toxicology., Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 4,30, 1984</p> <p>Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, Severe.<br/>Result:<br/>Effects on Newborn: Growth statistics (e.g., reduced weight gain).<br/>Effects on Newborn: Physical.<br/>- Union Carbide Data Sheet, Union Carbide Corp., 39 Old Ridgebury Rd., Danbury, CT 06817, Vol/p/yr: 4/25, 1958</p> <p>Standard Draize Test, Skin, Species: Rabbit, 810.0 MG, 24 H, Severe.</p> |
|-----------------------------------|--|

# SAFETY DATA SHEET

## Klean-Strip Fiberglass Paint Remover

Page: 8

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/25/2015

Result:  
Specific Developmental Abnormalities: Musculoskeletal system.  
- European Journal of Toxicology and Environmental Hygiene., For publisher information, see TOERD9, Paris France, Vol/p/yr: 9,171, 1976

CAS# 67-64-1:  
Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe.  
Result:  
Behavioral: Change in motor activity (specific assay).  
Behavioral: Alteration of classical conditioning.  
- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

### Carcinogenicity/Other Information:

IARC 2B - Possibly Carcinogenic to Humans  
IARC 3: Not Classifiable as to Carcinogenicity in Humans.  
ACGIH A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans  
ACGIH A4 - Not Classifiable as a Human Carcinogen.

| CAS #    | Hazardous Components (Chemical Name)                 | NTP      | IARC | ACGIH | OSHA |
|----------|--|----------|------|-------|------|
| 108-88-3 | Toluene {Benzene, Methyl-; Toluol}                   | n.a.     | 3    | A4    | n.a. |
| 75-09-2  | Dichloromethane {Methylene chloride; R-30; Freon 30} | Possible | 2B   | A3    | Yes  |
| 67-64-1  | Acetone {2-Propanone}                                | n.a.     | n.a. | A4    | n.a. |
| 67-56-1  | Methanol {Methyl alcohol; Carbinol; Wood alcohol}    | n.a.     | n.a. | n.a.  | n.a. |

## 12. ECOLOGICAL INFORMATION

**General Ecological Information:** No information available for this product as a whole.

## 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Dispose of in accordance with local, state, and federal laws.  
  
Do not place material in general trash.  
  
Do not allow material to enter bodies of water or sewers.

## 14. TRANSPORT INFORMATION

### LAND TRANSPORT (US DOT):

**DOT Proper Shipping Name:** Paint Related Material  
**DOT Hazard Class:** 3 FLAMMABLE LIQUID  
**UN/NA Number:** UN1263 **Packing Group:** II





# SAFETY DATA SHEET

## Klean-Strip Fiberglass Paint Remover

Page: 9  
Printed: 04/17/2015  
Revision: 04/17/2015  
Supersedes Revision: 03/25/2015

**Additional Transport Information:**

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

### 15. REGULATORY INFORMATION

**EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists**

| CAS #    | Hazardous Components (Chemical Name)                 | S. 302 (EHS) | S. 304 RQ   | S. 313 (TRI) |
|----------|--|--------------|-------------|--------------|
| 108-88-3 | Toluene {Benzene, Methyl-; Toluol}                   | No           | Yes 1000 LB | Yes          |
| 75-09-2  | Dichloromethane {Methylene chloride; R-30; Freon 30} | No           | Yes 1000 LB | Yes          |
| 67-64-1  | Acetone {2-Propanone}                                | No           | Yes 5000 LB | No           |
| 67-56-1  | Methanol {Methyl alcohol; Carbinol; Wood alcohol}    | No           | Yes 5000 LB | Yes          |

**This material meets the EPA**  Yes  No Acute (immediate) Health Hazard  
**'Hazard Categories' defined**  Yes  No Chronic (delayed) Health Hazard  
**for SARA Title III Sections**  Yes  No Fire Hazard  
**311/312 as indicated:**  Yes  No Sudden Release of Pressure Hazard  
 Yes  No Reactive Hazard

| CAS #    | Hazardous Components (Chemical Name)                 | Other US EPA or State Lists   |
|----------|--|---|
| 108-88-3 | Toluene {Benzene, Methyl-; Toluol}                   | CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 8A CAIR; CA PROP.65: Yes |
| 75-09-2  | Dichloromethane {Methylene chloride; R-30; Freon 30} | CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 8A CAIR; CA PROP.65: Yes |
| 67-64-1  | Acetone {2-Propanone}                                | CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: No     |
| 67-56-1  | Methanol {Methyl alcohol; Carbinol; Wood alcohol}    | CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: Yes           |

### 16. OTHER INFORMATION

**Revision Date:** 04/17/2015  
**Preparer Name:** W.M. Barr EHS Dept (901)775-0100

**Additional Information About** No data available.

**This Product:**

**Company Policy or Disclaimer:** The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.