Revision: 02/26/2020 Supersedes Revision: 08/06/2015

Gas Under Pressure, Liquefied gas Serious Eye Damage/Eye Irritation, Category 2 Germ Cell Mutagenicity, Category 1B Simple Asphyxiant	ID COMPANY IDENTIFICATION			
Web site address:www.wmbarr.comEmergency Contact:3E 24 Hour EmergencyInformation:W.M. Barr CustomIntended Use:Glass CleanerProduct Code:EGC3652. HAZAGas Under Pressure, Liquefied gasSerious Eye Damage/Eye Irritation, Category 2Germ Cell Mutagenicity, Category 1BSimple AsphyxiantImage: Colspan="2">Output:Image: Colspan="2">Output:GHS Signal Word:DangerGHS Hazard Phrases:Containers gas un Causes serious e May cause geneticGHS Precautionary Phrases:Obtain special ins Do not handle und Wash hands thord Wear protective g Use personal protGHS Response Phrases:IF IN EYES: Rins: present and easy IF exposed or cor If eye irritation perGHS Storage and Disposal 	Phone Number:           enue         (901)775-0100			
Information: W.M. Barr Custom Intended Use: Glass Cleaner Product Code: EGC365 2. HAZA Gas Under Pressure, Liquefied gas Serious Eye Damage/Eye Irritation, Category 2 Germ Cell Mutagenicity, Category 1B Simple Asphyxiant Containers gas un Causes serious e May cause genetic GHS Hazard Phrases: Containers gas un Causes serious e May cause genetic GHS Precautionary Phrases: Obtain special ins Do not handle un Wash hands thord Wear protective g Use personal prot GHS Response Phrases: IF IN EYES: Rinsipresent and easy IF exposed or corr If eye irritation per GHS Storage and Disposal Phrases: Store locked up. Protect from sunli Dispose of conter Medical Conditions Generally None known. Aggravated By Exposure: 3. COMPOSITION/ CAS # Hazardous Components (Chemical N 111-76-2 Ethanol, 2-Butoxy- {Ethylene glycol n-t (a glycol ether)} 68476-86-8 Liquified petroleum gas, sweetened {p isobutane, n-butane}				
Intended Use: Glass Cleaner Product Code: EGC365 2. HAZA Gas Under Pressure, Liquefied gas Serious Eye Damage/Eye Irritation, Category 2 Germ Cell Mutagenicity, Category 1B Simple Asphyxiant $\widehat{O}$ $\widehat{O}$ $\widehat{O}$ $\widehat{O}$ GHS Signal Word: Danger GHS Hazard Phrases: Containers gas un Causes serious e May cause geneti GHS Precautionary Phrases: Obtain special ins Do not handle und Wash hands thord Wear protective g Use personal prot GHS Response Phrases: IF IN EYES: Rinse present and easy IF exposed or cor If eye irritation per GHS Storage and Disposal Phrases: Protect from sunil Dispose of conter Medical Conditions Generally None known. Aggravated By Exposure: 3. COMPOSITION/ CAS # Hazardous Components (Chemical N 111-76-2 Ethanol, 2-Butoxy- {Ethylene glycol n-te (a glycol ether)} 68476-86-8 Liquified petroleum gas, sweetened {p isobutane, n-butane}	rgency Contact (800)451-8346			
Product Code:       EGC365         2. HAZA         Gas Under Pressure, Liquefied gas         Serious Eye Damage/Eye Irritation, Category 2         Germ Cell Mutagenicity, Category 1B         Simple Asphyxiant         Image: Containers gas unclasses         GHS Signal Word:         GHS Hazard Phrases:         GHS Precautionary Phrases:         Obtain special instant         Do not handle unt Wash hands thore         Wear protective g         Use personal prod         GHS Response Phrases:         IF IN EYES: Rinst present and easy IF exposed or cor If eye irritation per         GHS Storage and Disposal Phrases:         Phrases:         Store locked up. Protect from sunil Dispose of conter         Medical Conditions Generally None known. Aggravated By Exposure:         Store locked up Exposure:         Store locked up. Protect from sunil Dispose of conter         Medical Conditions Generally None known. Aggravated By Exposure:         Store locked up. Protect from sunil Dispose of conter         68476-86-8       Liquified petroleum gas, sweetened {p isobutane, n-butane}	ner Service (800)398-3892			
2. HAZA         Gas Under Pressure, Liquefied gas         Serious Eye Damage/Eye Irritation, Category 2         Germ Cell Mutagenicity, Category 1B         Simple Asphyxiant <b>Operation Operation GHS Signal Word: Danger</b> Containers gas un         Causes serious e         May cause genetit <b>GHS Precautionary Phrases:</b> Obtain special ins Do not handle und Wash hands thord Wear protective g Use personal proof <b>GHS Response Phrases: GHS Storage and Disposal</b> Protect from sunil Dispose of conter <b>Actourtoontitions Generally</b> None known. <b>Actourtoontitions Generally</b> None known. <b>Actourtoottotions Components (Chemical N</b> 111-76-2 <b>Contentical Conditions Components (Chemical N</b> 111-76-2 <b>Contentical Conditions Components (Chemical N</b> 111-76-2         Containers gas und Dispose of conter <b>Contentical N</b>				
Gas Under Pressure, Liquefied gas Serious Eye Damage/Eye Irritation, Category 2 Germ Cell Mutagenicity, Category 1B Simple Asphyxiant				
Serious Eye Damage/Eye Irritation, Category 2 Germ Cell Mutagenicity, Category 1B Simple Asphyxiant	ARDS IDENTIFICATION			
GHS Hazard Phrases:       Containers gas un Causes serious e May cause genetil         GHS Precautionary Phrases:       Obtain special instibution on thandle unt Wash hands thore Wear protective guse personal protect from sunling bispose of contertive guse for contertive guse for a start gusta gu	A			
GHS Hazard Phrases:       Containers gas un Causes serious e May cause genetil         GHS Precautionary Phrases:       Obtain special ins Do not handle unt Wash hands thord Wear protective g Use personal prot         GHS Response Phrases:       IF IN EYES: Rinse present and easy IF exposed or cor If eye irritation per         GHS Storage and Disposal Phrases:       Store locked up. Protect from sunli Dispose of conter         Medical Conditions Generally None known.       None known.         Aggravated By Exposure:       3. COMPOSITION/I         CAS #       Hazardous Components (Chemical N (a glycol ether))         68476-86-8       Liquified petroleum gas, sweetened {p isobutane, n-butane}				
GHS Response Phrases:       Do not handle unt Wash hands thore Wear protective guse personal protectinterprotectend guste personal protective gusetend guse	•			
GHS Response Phrases:       IF IN EYES: Rinst present and easy IF exposed or con If eye irritation per GHS Storage and Disposal Phrases:       Store locked up. Protect from sunli Dispose of conter         Medical Conditions Generally None known.       Aggravated By Exposure: <b>3. COMPOSITION/</b> CAS # Hazardous Components (Chemical N         111-76-2       Ethanol, 2-Butoxy- {Ethylene glycol n-b (a glycol ether)}         68476-86-8       Liquified petroleum gas, sweetened {p isobutane, n-butane}	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required.			
GHS Storage and Disposal Phrases:       Store locked up. Protect from sunli Dispose of conter         Medical Conditions Generally None known. Aggravated By Exposure:       Medical Conditions Generally None known.         Aggravated By Exposure:       3. COMPOSITION/I         CAS #       Hazardous Components (Chemical N (a glycol ether))         68476-86-8       Liquified petroleum gas, sweetened {p isobutane, n-butane}	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention/advice. If eye irritation persists, get medical advice/attention.			
Aggravated By Exposure:         3. COMPOSITION/I         CAS #       Hazardous Components (Chemical N         111-76-2       Ethanol, 2-Butoxy- {Ethylene glycol n-b (a glycol ether)}       Ethanol, 2-Butoxy- {Ethylene glycol n-b (a glycol ether)}         68476-86-8       Liquified petroleum gas, sweetened {p isobutane, n-butane}				
3. COMPOSITION/I         CAS #       Hazardous Components (Chemical N         111-76-2       Ethanol, 2-Butoxy- {Ethylene glycol n-b (a glycol ether)}         68476-86-8       Liquified petroleum gas, sweetened {p isobutane, n-butane}				
CAS #Hazardous Components (Chemical N111-76-2Ethanol, 2-Butoxy- {Ethylene glycol n-b (a glycol ether)}68476-86-8Liquified petroleum gas, sweetened {p isobutane, n-butane}	INFORMATION ON INGREDIENTS			
<ul> <li>111-76-2 Ethanol, 2-Butoxy- {Ethylene glycol n-b (a glycol ether)}</li> <li>68476-86-8 Liquified petroleum gas, sweetened {p isobutane, n-butane}</li> </ul>				
isobutane, n-butane}	,			
Additional Chemical Specific percentage	propane, 5.0 -10.0 %			
Information	e of composition is being withheld as a trade secret.			
Licensed to W.M. Barr and Company	GHS forma			

Page: 2 of 6

	4. FIRST AID MEASURES			
Emergency and First Aid Procedures:	Skin: Immediately begin washing the skin thoroughly with large amounts of water and mild soap, if available, while removing contaminated clothing. Seek medical attention if irritation persists.			
	Eyes: Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes, then seek immediate medical attention.			
	Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.			
	Ingestion: If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down.			
	5. FIRE FIGHTING MEASURES			
Flash Pt:	No data.			
Explosive Limits:	LEL: No data. UEL: No data.			
Autoignition Pt:	No data.			
Suitable Extinguishing Medi	a:Non-combustible liquid - use extinguishing media for underlying cause of fire.			
Unsuitable Extinguishing Media:	None known.			
Fire Fighting Instructions:	Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.			
Flammable Properties and Hazards:	FLASHPOINT of Liquid Concentrate: No flash to boiling. The liquid concentrate does not exhibit a flashpoint per the Setaflash Closed Cup test method.			
	The heat of combustion of the aerosol product is less than 4 kJ/g.			
Hazardous Combustion Products:	Aerosol flame extension testing does not project flame or exhibit flash back. No data available.			

Revision: 02/26/2020 Supersedes Revision: 08/06/2015

	6. ACCIDENT	AL RELEASE MEASURES			
Steps To Be Taken In Case Material Is Released Or Spilled:	For small spills: Al chemical waste co	bsorb spill with inert material (e.g. dry sand or ntainer.	earth), then place in a		
opineu.	For large spills: Wear appropriate PPE and keep all unecessary personnel out of the area. Stop spill at the source, dike ahead of the spill if possible, and contain the spill. Recover as much as possible and use absorbent material to collect the remaining lique Prevent runoff from entering drains, sewers, or bodies of water.				
	Dispose of accordi	ing to all applicable local, state, and federal re	gulations.		
	7. HAND	DLING AND STORAGE			
Precautions To Be Taken in Handling:	Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.				
	Avoid breathing of	vapors or mist. Avoid contact with eyes and s	kin.		
	A source of clean water should be available in or near the work area for flushing of the eyes and skin if contact occurs.				
8. EXP	OSURE CONT	TROLS/PERSONAL PROTECTION	ON		
CAS # Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations		
111-76-2 Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	ACGIH TLV	TLV: 20 ppm			
	OSHA PELs	PEL: 50 ppm			
Respiratory Equipment (Specify Type):	When used by the consumer following directions for use and with adequate ventilation, respiratory protection should not be needed.				
Eye Protection:	Safety glasses sho	uld be worn during normal handling of this ma	terial.		
	Where contact with the eyes or face is likely, a faceshield or chemical splash goggles should be worn to prevent eye contact.				
Protective Gloves:	Wear gloves with as much resistance to the chemical ingredients as possible. Glove materials such as nitrile rubber may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.				
Other Protective Clothing:	Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.				
Engineering Controls (Ventilation etc.):		ally not required when handling or using this pl inants below the exposure limit.	oduct to keep exposure		
	•	sures, local exhaust ventilation, or other engine els below recommended exposure limits.	eering controls to		

	Supersedes Revision: 08/06/2015
Work/Hygienic/Maintenance Practices:	Wash hands thoroughly after use and before eating, drinking, smoking, or using the restroom.
	Do not eat, drink, or smoke in the work area.
	Discard any clothing or other protective equipment that cannot be decontaminated.
	Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.
9.	PHYSICAL AND CHEMICAL PROPERTIES
Physical States:	[ X ] Gas [ X ] Liquid [ ] Solid
Appearance and Odor:	No data available.
pH:	9.85 - 10.85
Melting Point:	No data.
Boiling Point:	No data.
Flash Pt:	No data.
Evaporation Rate:	No data.
Flammability (solid, gas):	No data available.
Explosive Limits:	LEL: No data. UEL: No data.
Vapor Pressure (vs. Air or mm Hg):	No data.
Vapor Density (vs. Air = 1):	No data.
Specific Gravity (Water = 1):	0.9937
Solubility in Water:	No data.
Octanol/Water Partition	No data.
Coefficient:	
Autoignition Pt:	No data.
Decomposition Temperature:	No data.
Viscosity:	No data.
	10. STABILITY AND REACTIVITY
Stability:	Unstable [ ] Stable [ X ]
Conditions To Avoid - Instability:	No data available.
Incompatibility - Materials To Avoid:	Strong acids and oxidizers.
Hazardous Decomposition or Byproducts:	Aldehydes, ketones, organic acids
Possibility of Hazardous Reactions:	Will occur [ ] Will not occur [ X ]
Conditions To Avoid - Hazardous Reactions:	No data available.

Revision: 02/26/2020 Supersedes Revision: 08/06/2015

		11. TOXICOLOGICA	L INFOR	MATION				
Toxicological Information:		This product has not been tested as a whole. Refer to section 2 for acute and chronic effects.						
		CAS# 111-76-2: Acute toxicity, LC50, Inhalation	Rat 450.01					
		Result:	, 11al, 400.01	1 101, 4 1 1.				
		Behavioral: Ataxia.						
		<ul> <li>Nutritional and Gross Metabolic:Weight loss or decreased weight gain.</li> <li>Toxicology and Applied Pharmacology, Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 68,405, 1983</li> </ul>						
		Acute toxicity, LD50, Skin, Species: Rabbit, 220.0 MG/KG. Result:						
		Effects on Embryo or Fetus: Ex	•	· •	., placenta, u	mbilical cord).		
		Effects on Embryo or Fetus: Ot Specific Developmental Abnorr		•	em.			
		- Dow Chemical Company Reports., Dow Chemical USA, Health and Environment Research, Toxicology Research Lab, Midland, MI 48640, Vol/p/yr: MSD-46,						
		Acute toxicity, LD50, Oral, Rat, 250.0 mg/kg. Result:						
		Lungs, Thorax, or Respiration: Changes in pulmonary vascular resistance.						
		Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, Severe. Result:						
		Effects on Newborn: Apgar score (human only).						
		Effects on Newborn: Other neonatal measures or effects. Effects on Newborn: Drug dependency.						
		- American Journal of Ophthalr Suite 1415, Chicago, IL 60611,	nology., Opht		, 435 N. Mich	igan Ave.,		
Carcinogenic	ity/Other	IARC 3: Not Classifiable as to	-	•				
Information: CAS #	Hazardaya Car	ACGIH A3 - Confirmed Animal			elevance to H ACGIH			
111-76-2		nponents (Chemical Name) <pre>(y- {Ethylene glycol n-butyl ether, ()</pre>	NTP a glycol n.a.	IARC 3	ACGIH A3	OSHA n.a.		
	ether)}							
68476-86-8	Liquified petrole	um gas, sweetened {propane, isobu	itane, n.a.	n.a.	n.a.	n.a.		
		12. ECOLOGICAL	INFORM	ATION				
General Ecolo Information:	ogical	This product has not been teste	ed as a whole					
		13. DISPOSAL COI	<b>NSIDERA</b>	TIONS				
Waste Dispos	sal Method:	Dispose of in accordance with	local, state, a	nd federal laws.				
		Do not place material in genera	al trash.					
		Do not allow material to enter b	odies of wate	er or sewers.				

Page: 6 of 6

			Supe	rsedes Revision: 08/06/2015	
. ,	e: Aerosols, non-flammable	•			
	NON-FLAMMABLE GIS				
	15. REGULATOR	Y INFORMA	TION		
uperfund Amendme	ents and Reauthorization Act o	of 1986) Lists			
		<b>S. 302 (EHS)</b> No	<b>S. 304 RQ</b> No	<b>S. 313 (TRI)</b> Yes-Cat. N230	
· ·	iquified petroleum gas, sweetened {propane,		No	No	
Hazardous Comp	oonents (Chemical Name)	Other US EPA o	r State Lists		
Ethanol, 2-Butoxy (a glycol ether)}	- {Ethylene glycol n-butyl ether,				
· ·	•	TSCA: Inventory			
	16. OTHER IN	FORMATIO	N		
e:	02/26/2020				
ne:	W.M. Barr EHS Dept (901)	775-0100			
This Product:       and is subject to certain         Act. These requirements       required for safety data		ling requirements er from the classi ts (SDS). The pro	under the Federa fication criteria an oduct label also in	al Hazardous Substances d hazard information cludes other important	
-	as of the effective date shown any kind. Employers should information gathered by them and completeness of informa materials and the safety and must be determined by the us	n above. This inf use this informat and must make tion from all sour health of employ	formation is furnis ion only as a supp independent dete ces to assure pro ees. Any use of t	hed without warranty of plement to other ermination of suitability per use of these his data and information	
	er Shipping Name rd Class: mber: uperfund Amendme Hazardous Comp Ethanol, 2-Butoxy- (a glycol ether)} Liquified petroleum isobutane, n-butar Hazardous Comp Ethanol, 2-Butoxy- (a glycol ether)} Liquified petroleum isobutane, n-butar e: he: formation About	rd Class: 2.2 NONFLA mber: UN1950	ar Shipping Name:       Aerosols, non-flammable, Ltd. Qty.         rd Class:       2.2       NONFLAMMABLE GAS         mber:       UN1950         upperfund Amendments and Reauthorization Act of 1986) Lists         Hazardous Components (Chemical Name)       S. 302 (EHS)         Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}       No         Liquified petroleum gas, sweetened {propane, n-butane}       Other US EPA o         Hazardous Components (Chemical Name)       CAA HAP,ODC: TSCA: Inventory         Liquified petroleum gas, sweetened {propane, isobutane, n-butane}       Other US EPA o         Hazardous Components (Chemical Name)       CAA HAP,ODC: TSCA: Inventory         Liquified petroleum gas, sweetened {propane, isobutane, n-butane}       No         Hazardous Components (Chemical Name)       CAA HAP,ODC: TSCA: Inventory         Liquified petroleum gas, sweetened {propane, isobutane, n-butane}       CAA HAP,ODC: TSCA: Inventory         Stoutane, n-butane}       The information (901)775-0100         formation About       This product is regulated by the United States and is subject to certain labeling requirements Act. These requirements differ from the classi required for safety data sheets (SDS). The provinformation, including directions for use, and su using the product.         licy or       The information contained herein is presented as of the effective date shown above. This ind any kind. Employers should use this informati in	SPORT (US DOT):         er Shipping Name:       Aerosols, non-flammable, Ltd. Qty.         rd Class:       2.2       NONFLAMMABLE GAS         mber:       UN1950 <b>IDENTIFICATION Automation Automation</b> Aerosols, non-flammable, Ltd. Qty.         rd Class:         2.2         NONFLAMMABLE GAS         mission <b>DENTIFICATION Automation Automation Automation Colspan="2" Automation Automation</b>	