



# AIRCRAFT® Paint Remover

---

GAR343, QAR343  
EAR322

Gallon, Quart Liquid  
18oz Aerosol



- Starts Working in 5 Minutes (aerosol in 15 minutes)
- Lifts Multiple Layers
- Removes acrylics, epoxies, enamels, lacquers, polyurethanes, and most other automotive finishes
- Clings well to vertical surfaces
- Water Rinsable

---

## **FINISH REMOVAL TIPS**

1. KLEAN-STRIP® AIRCRAFT® Paint Remover begins to work in as little as 5 minutes. Once applied, allow time for the remover to do the work. Let stand until finish is completely blistered or liquefied. The time will vary from 5 to 45 minutes for most finishes.
2. Scratching or abrading the finish will often speed up the stripping action.
3. **Always apply a generous amount of remover. Thickly daubing remover onto the surface, rather than brushing, provides better coverage. Thin coats can dry too quickly for the remover to work effectively.**
4. On particularly tough finishes, and to minimize evaporation, secure a 2 – 3 mil polyethylene film over wet remover. For best results, let the remover stand up to two hours, and if necessary, repeat with a second application.
5. If stripper dries on the surface, scrape loosened portions and reapply as needed.
6. Mask seams and trim openings to prevent bleed-back stripping of new finish.

\*Not intended for use on aircraft.





# AIRCRAFT® Paint Remover

	<b>GAR343/QAR343</b>	<b>EAR322</b>
<b>Appearance</b>	Thick, orange to brown opaque paste with strong ammonia odor	Yellow to orange clinging liquid
<b>Vapor Density</b>	Heavier Than Air	
<b>Percent Volatile</b>	95% by weight	98% by weight
<b>Flash Point</b>	No Flash to Boiling	N/A
<b>CPSC Flammability Classification</b>	Not a Flammable or Combustible Liquid	Flammable
<b>Boiling Range</b>	105°F to 300°F	N/A
<b>Max VOC</b>	11.1%	Less than 50%
<b>Storage</b>	Store in a cool place. Prolonged exposure to temps in excess of 90°F may cause can to leak or swell. Do not reuse container. Once opened, remover should be used within 6 months or disposed of properly to avoid can deterioration.	Replace overcap on container after each use. Contents under pressure. Do not puncture, incinerate or store above 120°F. Exposure to heat or prolonged exposure to sun can cause bursting.
<b>Density</b>	9.8 lb/gal	10.5 lb/gal
<b>Shelf Life</b>	2 years from date of manufacture, in an unopened container	
<b>DOT</b>	UN1760, Corrosive Liquid, N.O.S., 8, PGI (Ammonium Hydroxide, Methylene Chloride)	UN1950, AEROSOLS, flammable, 2.1, Limited Quantity
<b>HAPS</b>	Methylene Chloride, Methanol, Xylene, Ethyl Benzene	Methylene Chloride, Methanol
<b>Coverage</b>	25 – 50 sq. ft. per can	10 – 15 sq. ft. per can
<b>VOC Category</b>	Paint Removers or Strippers	

## ORDERING INFORMATION

Product	Size	Pack	Lbs	Cube Ft.	Width	Depth	Height	UPC Code	Pallet Qty
QAR343	QT	6	17	.347	7 10/16	9 11/16	8 2/16	030192343159	125 cases
GAR343	GL	2	22	.404	7 1/16	8 14/16	11 2/16	030192343258	104 cases
EAR322	18oz	4	6	.194	5 11/16	5 11/16	10 6/16	030192322994	168 cases

©2009 W.M. Barr & Co., Inc.  
P.O. Box 1879  
Memphis, TN 38101  
800.238.2672  
www.bulldogsticks.com  
www.kleanstripauto.com

