Page: 1 of 8

SAFETY DATA SHEET Prep All Color Check Aerosol

Revision: 06/12/2019 Supersedes Revision: 06/28/2018

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Prep All Color Check Aerosol

Company Name: W. M. Barr Phone Number:

2105 Channel Avenue (901)775-0100 Memphis. TN 38113

Web site address: www.wmbarr.com

Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346 **Information:** W.M. Barr Customer Service (800)398-3892

Intended Use: Temporary clearcoat for color matching

Product Code: ECC366

2. HAZARDS IDENTIFICATION

Flammable Aerosols, Category 1
Gas Under Pressure, Liquefied gas
Germ Cell Mutagenicity, Category 1B
Toxic To Reproduction, Category 2

Specific Target Organ Toxicity (single exposure), Category 3
Specific Target Organ Toxicity (repeated exposure), Category 2

Aspiration Toxicity, Category 1

Simple Asphyxiant









GHS Signal Word: Danger

GHS Hazard Phrases: Flammable aerosol.

Containers gas under pressure; may explode if heated.

May be fatal if swallowed and enters airways.

May cause respiratory irritation. May cause drowsiness or dizziness.

May cause genetic defects.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

GHS Precautionary Phrases: Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or any other ignition source. Pressurized container: Do not pierce or burn, even after use.

Do not breathe gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.
Use personal protective equipment as required.

GHS Response Phrases: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

IF exposed or concerned: Get medical attention/advice.

Call a POISON CENTER or doctor/physician if you feel unwell.

Get medical attention/advice if you feel unwell.

Do NOT induce vomiting.

GHS Storage and Disposal

Phrases: Store locked up.

Destant former all also and

Protect from sunlight and store in well-ventilated place.

Store container tightly closed in well-ventilated place.

Licensed to W.M. Barr and Company

GHS format

Page: 2 of 8

SAFETY DATA SHEET Prep All Color Check Aerosol

Revision: 06/12/2019 Supersedes Revision: 06/28/2018

Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container according to local, state and federal regulations.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute and Chronic):

Inhalation Acute Exposure Effects:

Vapor concentration may cause headache, dizziness, irritation of the respiratory tract, eye irritation, stupor, depression of the central nervous system, watering of the eyes, weakness, nausea, muscle twitches, and kidney effects. Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal. Severe overexposure may cause convulsions, unconsciousness, depression of the central nervous system, irritation of the respiratory tract, coma, and death.

Skin Contact Acute Exposure Effects:

May cause irritation, drying of the skin, burning sensation, redness, swelling, and/or blisters. Absorption may cause or increase severity of symptoms listed under inhalation. If the skin is damaged, absorption increases. Prolonged or repeated contact may cause moderate to severe dermatitis. Chronic symptoms may include drying, swelling, scaling, blistering, cracking, and severe tissue damage.

Eye Contact Acute Exposure Effects:

May cause irritation, burning sensation, redness, swelling, watering of the eyes, and/or blurred vision.

Ingestion Acute Exposure Effects:

Harmful or fatal is swallowed. Causes irritation of the stomach and intestines, resulting in nausea and vomiting. May cause burning sensation in mouth and stomach, headache, loss of appetite, weakness, muscle twitches, loss of coordination, convulsions, unconsciousness, coma, and death.

If the material enters the lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. This can result in severe lung damage or death.

Chronic Exposure Effects:

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Repeated or prolonged skin contact may cause redness, irritation, and scaling of the skin. May cause skin irritation, anemia, bone marrow damage, some loss of memory, heart palpitations, liver damage, kidney damage, and jaundice.

Target Organs: lungs, central nervous system, brain, mucous membranes, skin, eyes, liver, and kidneys.

Medical Conditions Generally Pre-existing central nervous system disease, neurological conditions, skin disorders, **Aggravated By Exposure:** liver or kidney function, or chronic respiratory diseases.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS#	Hazardous Components (Chemical Name)	Concentration
64742-49-0	Hydrotreated light naphtha	30.0 -60.0 %
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	10.0 -30.0 %
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	5.0 -10.0 %

Page: 3 of 8

SAFETY DATA SHEET Prep All Color Check Aerosol

Revision: 06/12/2019 Supersedes Revision: 06/28/2018

79-20-9 Methyl acetate (Methyl ester of acetic acid) 30.0 -60.0 %

Additional Chemical

Specific percentage of composition is being withheld as a trade secret.

nformation

4. FIRST AID MEASURES

Emergency and First Aid

First Aid Inhalation:

Procedures:

If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or

artificial respiration until medical assistance can be rendered.

Skin contact:

Wash with soap, if available, and large quantities of water for at least 15 minutes. Seek

medical attention if irritation from contact persists.

Eye contact:

Immediately flush eyes with water, remove nay contact lens, continue flushing with water

for at least 15 minutes. Get medical attention.

Ingestion:

Do not induce vomiting. Call your poison control center, hospital emergency room, or

physician immediately.

Signs and Symptoms Of

Exposure:

Primary routes of exposure: Inhalation, ingestion, and dermal.

Note to Physician: Treatment of overexposure should be directed at the control of symptoms and the clinical

condition of the patient.

5. FIRE FIGHTING MEASURES

Flammable - Level 3 Aerosol

Flash Pt: 52.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)

Explosive Limits: LEL: No data. UEL: No data.

Autoignition Pt: No data.

Suitable Extinguishing Media: Use carbon dioxide, dry powder, or foam.

Unsuitable Extinguishing

Media:

Solid streams of water may be ineffective and spread material.

Fire Fighting Instructions: Self-contained respiratory protection should be provided for fire fighters fighting fires in

buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from containers that have been

exposed to intense heat or flame.

Flammable Properties and

Hazards:

Flashpoint of liquid: 52 degrees F

Flashpoint of propellant: -132 degrees F

Hazardous Combustion

Carbon monoxide, carbon dioxide

Products:

SAFETY DATA SHEET Prep All Color Check Aerosol

Revision: 06/12/2019 Supersedes Revision: 06/28/2018

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled: Danger! Flammable! Keep away from heat, sparks, flame and all other sources of ignition. Vapors may cause fire. Vapors may travel long distances to other areas and rooms away from work site. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition anywhere in the structure, dwelling or building during use and until all vapors are gone from work site and all areas away from the work site. Keep away from electrical outlets and switches. Beware of static electricity that may be generated by synthetic clothing and other sources.

Use non-metallic or non-sparking tools. Properly bond and ground all equipment.

Clean-up:

Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources, keep flares, smoking or flames out of hazard area.

Small spills:

Take up the spilled liquid with sand, earth, or other noncombustible absorbent material and place in a plastic container where applicable.

Large spills:

Dike far ahead of spill for later disposal.

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Various application methods can dictate use of additional protective safety equipment,

Precautions To Be Taken in Storing:

Other Protective Clothing:

Store in a cool, dry place. Do not store near flames or at elevated temperatures.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8. EXPOSURE CONTROLS/PERSONAL PROTECTION				
CAS#	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
64742-47-8 distillate (pe	Hydrotreated light etroleum, mineral spirits)	ACGIH TLV	TLV: 200 mg/m3	
79-20-9 Mester of ace	Methyl acetate (Methyl etic acid)	ACGIH TLV	TWA: 200 ppm STEL: 250 ppm	
		OSHA PELs	TWA: 610 mg/m3 (200 ppm)	
Respirator (Specify T	ype):	ventilation under en appropriate TLV or e not feasible, use pro	d work place and other regular users. Use of gineered air control systems designed to presexposure limits. For occasional use, where experly maintained and properly fitted NIOSH fors. A dust mask does not provide protection	vent exceeding engineered air control is approved respirator for
Eye Protec		Chemical goggles, c contact, irritation, or	or face shields are recommended to safegual injury.	rd against potential eye
Protective	J	materials such as ni	s much resistance to the chemical ingredients trile provide protection. Glove selection shows and conditions of use. Consult your glove	uld be based on

such as impermeable aprons, etc., to minimize exposure. Before reuse, thoroughly Licensed to W.M. Barr and Company

GHS format

SAFETY DATA SHEET **Prep All Color Check Aerosol**

Revision: 06/12/2019 Supersedes Revision: 06/28/2018

clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such

as gloves or shoes.

Engineering Controls

(Ventilation etc.):

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering -- Stop -- ventilation is inadequate. Leave area immediately.

Work/Hygienic/Maintenance A source of clean water should be available in the work area for flushing eyes and skin.

Practices:

Do not eat, drink, or smoke in the work area.

Wash hands thoroughly after use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States: [X]Gas [X] Liquid [] Solid

Free and clear, liquid. Appearance and Odor:

pH: No data. No data. Melting Point: **Boiling Point:** 190.00 F

Flash Pt: 52.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)

Evaporation Rate: No data.

No data available. Flammability (solid, gas):

Explosive Limits: LEL: No data. UEL: No data.

No data.

Vapor Pressure (vs. Air or

mm Hg):

Vapor Density (vs. Air = 1): > 1 Specific Gravity (Water = 1): 0.816 Solubility in Water: Insoluble Octanol/Water Partition No data.

Coefficient:

N.A. Percent Volatile: No data. **Autoignition Pt: Decomposition Temperature:** No data. Viscosity: No data. MIR = 0.75Additional Physical

Information

10. STABILITY AND REACTIVITY

Unstable [] Stable [X] Stability:

Conditions To Avoid -No data available.

Instability:

Incompatibility - Materials To Incompatible with strong oxidizing agents.

Avoid:

Hazardous Decomposition or Thermal decomposition may produce carbon monoxide and carbon dioxide.

Byproducts:

Possibility of Hazardous Will occur [] Will not occur [X]

Reactions:

Conditions To Avoid -No data available.

Hazardous Reactions:

SAFETY DATA SHEET Prep All Color Check Aerosol

Product has not been tested as a whole. Refer to section 2 for acute and chronic effects.

Revision: 06/12/2019 Supersedes Revision: 06/28/2018

11. TOXICOLOGICAL INFORMATION

TI. TOXIOGEOGICAE III ORMATICI

Carcinogenicity/Other IARC 3: Not Classifiable as to Carcinogenicity in Humans. ACGIH A4 - Not Classifiable as a Human Carcinogen.

CAS#	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
64742-49-0	Hydrotreated light naphtha	n.a.	n.a.	n.a.	n.a.
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	n.a.	n.a.	n.a.	n.a.
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	n.a.	n.a.	A4	n.a.
79-20-9	Methyl acetate (Methyl ester of acetic acid)	n.a.	n.a.	n.a.	n.a.

12. ECOLOGICAL INFORMATION

General Ecological

Toxicological Information:

Information:

Product has not been tested as a whole.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose in accordance with applicable local, state, and federal regulations.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Aerosols, flammable

DOT Hazard Class: 2.1 FLAMMABLE GAS

UN/NA Number: UN1950



Additional Transport

Information:

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists					
CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)	
64742-49-0	Hydrotreated light naphtha	No	No	No	
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	No	No	No	
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	No	No	No	
79-20-9	Methyl acetate (Methyl ester of acetic acid)	No	No	No	
CAS#	Hazardous Components (Chemical Name)	Other US EPA or S	State Lists		
64742-49-0	Hydrotreated light naphtha	TSCA: Inventory			
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	TSCA: Inventory			
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	TSCA: Inventory			
79-20-9	Methyl acetate (Methyl ester of acetic acid)	TSCA: Inventory, 8	BA PAIR		

Page: 7 of 8

SAFETY DATA SHEET Prep All Color Check Aerosol

Revision: 06/12/2019 Supersedes Revision: 06/28/2018

Regulatory Information:

Additional Regulatory

Information

This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

16. OTHER INFORMATION

Revision Date: 06/12/2019

Preparer Name: W.M. Barr EHS Dept (901)775-0100

Additional Information About No data available.

This Product:

Company Policy or

Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.