DIRECTIONS FOR USE

Protect hands with solvent-resistant gloves and eyes with chemical splash goggles.

Directions for Uses: 1. Remove loose rust scale using a scraper or wire brush. 2. Remove oil and dirt using Prep-All® Wax & Grease Remover or other hard surface cleaner 3. Shake well Pour Rust Converter into a disposable container. Do not pour any used product back into the bottle. 4. Using a brush or sponge, apply a thin layer of Rust Converter to rusted areas only. Product may stain non-rusted finishes. Clean spatters immediately with soap and water. 5. A black coating will appear over rusted areas in 15-30 minutes. Protect from moisture. Allow the converted coating to dry for 24 hours prior to sanding or painting. 6. Apply topcoat following paint manufacturer's instructions.

Note: This product may not be compatible with all surfaces and all conditions surrounding application. Before applying to any surface, always test product in a small inconspicuous area to ensure no damage will result. Do not freeze. All rusts are not the same due to moisture content and weather exposure. This can cause variations in the primer color produced (dark brown to black). However, the rust has been converted and the surface protected. Severely rusted surfaces may be too damaged for restoration. Avoid direct sunlight or strong breezes.

CAUTION: EYE IRRITANT. Contains Vinyl Acrylic Copolymer and Tannic Acid. Avoid contact with eyes and prolonged contact with skin. Do not ingest.

FIRST AID: In case of eye contact, flush thoroughly with water for 15 minutes and get immediate medical attention. For skin contact, wash thoroughly with soap and water. If irritation persists, get medical attention. If ingested, contact physician immediately.

KEEP OUT OF REACH OF CHILDREN

For assistance call:
The Barr Help Line 1-800-398-3892
Monday - Friday 8am - 4:30pm Central Time

Cbarr.

Product # WRC22 @2011 W.M. Barr & Co. Inc. Memphis, TN 38113 www.kleanstripauto.com All rights reserved. Label design is a trademark of W.M. Barr & Co., Inc. J5575



