



AIRCRAFT® Non-Methylene Chloride Paint Remover

GAR2000, QAR2000
EAR2000

Gallon, Quart Liquid
15oz Aerosol



- Strips to bare metal within 45 minutes
- Removes acrylics, epoxies, enamels, lacquers, polyurethanes, and most other automotive finishes
- Works on metal, fiberglass and flexible & rigid plastics
- Patented and VOC Compliant in all states

DIRECTIONS FOR USE

Carefully read all instructions on the label and cautions on the SDS prior to use. Protect hands with solvent-resistant gloves and eyes with chemical splash goggles. Make sure the work area is properly ventilated.

1. Mask seams and trim openings. This will prevent bleed-back stripping of new finish.
2. Sand the surface prior to application, using 80 – 240 grit sandpaper.
3. Shake well.
4. *GAR2000/QAR2000 Application* – Pour remover onto the surface. Use a chemical resistant spreader, making sure to maintain a thick coat. Do not break the surface of the remover or spread too thin. Apply to one section at a time, up to 3 ft. x 3 ft. Apply in one direction only.
5. *EAR2000 Application* – Hold can in an upright position and point arrow on top of button away from you. Spray at a distance of approximately 6-8 inches from the surface. To avoid sagging on vertical surfaces, use a back and forth motion to apply a generous, even coat. Apply to one section at a time, up to 3 ft. x 3 ft.
6. Allow remover to work until finish is blistered or softened completely, generally within 45 minutes. To speed up removal time, scuff prior to application and cover the surface with plastic. See below tips for recommendations.
7. Remove paint with a flexible plastic scraper, then rinse with water or mineral spirits to remove any residue.




FINISH REMOVAL TIPS

- Scratching or abrading the finish will often speed up the stripping action. Use 80 – 240 grit sandpaper to break the surface.
- **Always apply a generous amount of remover. Thickly pouring remover onto the surface, rather than brushing, provides better coverage and performance. Thin coats can dry too quickly for the remover to work effectively.**
- On particularly tough finishes, and to minimize evaporation, secure a 2 – 3 mil polyethylene film over wet remover. For best results, let the remover stand up to one hour, and if necessary, repeat with a second application.
- If stripper dries on the surface, scrape loosened portions and reapply as needed.
- This product may not be compatible with all surfaces and all conditions surrounding application. Before applying to any surface, always test product in a small, inconspicuous area to ensure no damage will result.
- Prime bare metal as soon as possible to prevent flash rust.
- For best results apply at temperatures between 65F and 85F and avoid direct sunlight.
- Intended for use on automotive surfaces. Designed specifically to remove cured two-component urethanes and epoxy finishes.
- Do not apply to floors or any other large surface areas because fire and health safety risks will increase dramatically. Always wear chemical splash goggles and chemical-resistant gloves when handling this product. A dust mask will not provide protection against vapors.
- **DO NOT USE TO STRIP BATHTUBS**
- Not intended for use on aircraft.





AIRCRAFT® Non-Methylene Chloride Paint Remover

	GAR2000/QAR2000	EAR2000
Appearance	Opaque orange/blush red viscous liquid	Opaque orange/yellow viscous liquid
Flash Point	0°F	0°F
CPSC Flammability Classification	Extremely Flammable	Extremely Flammable
VOC Category	Paint Remover	Paint Remover
Max VOC	50%	50%
Actual VOC	390.3 g/L 3.257 lb/gal 46%	49.5%
Storage	Store in a cool place. Prolonged exposure to temps in excess of 90°F may cause can to leak or swell. Do not reuse container. Once opened, remover should be used within 6 months or disposed of properly to avoid can deterioration.	Replace overcap on container after each use. Contents under pressure. Do not puncture, incinerate or store above 120°F. Exposure to heat or prolonged exposure to sun can cause bursting.
Density	7.3 lb/gal	7.3 lb/gal
Shelf Life	2 years from date of manufacture, in an unopened container	
Prop 65	 CA WARNING: This product can expose you to chemicals including Tetrahydrofuran, which are known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov .	
DOT	UN3469, Paint Related Material, Flammable, Corrosive 3 (8,) PGII (Quart is Limited Quantity)	UN1950, AEROSOLS, flammable, 2.1, Limited Quantity

ORDERING INFORMATION

Product	Size	Pack	Lbs	UPC Code	Pallet Qty
QAR2000	QT	6	2.83	0-30192-02000-5	750
GAR2000	GL	2	5.48	0-30192-10000-4	208
EAR2000	15oz	4	1.5	0-30192-02001-2	672

©2019 W.M. Barr & Co., Inc.

