

## Bulldog Adhesion Promoter Aerosol Formula

Printed: 08/24/2023

Revision: 08/24/2023

Supersedes Revision: 08/21/2023

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Bulldog Adhesion Promoter Aerosol Formula  
**Company Name:** W. M. Barr  
 2105 Channel Avenue  
 Memphis, TN 38113  
**Web site address:** www.wmbarr.com  
**Emergency Contact:** 3E 24 Hour Emergency Contact (800)451-8346  
**Information:** W.M. Barr Customer Service (800)398-3892  
**Intended Use:** Paint adhesion.  
**Product Code:** ETPO123B, ETPO123BCN

## 2. HAZARDS IDENTIFICATION

Flammable Gases, Category 1  
 Gas Under Pressure, Compressed gas  
 Flammable Liquids, Category 2  
 Self-Reactive Substances, Type G  
 Simple Asphyxiant  
 Skin Corrosion/Irritation, Category 2  
 Serious Eye Damage/Eye Irritation, Category 2  
 Skin Sensitization, Category 1  
 Germ Cell Mutagenicity, Category 2  
 Toxic To Reproduction, Category 2  
 Specific Target Organ Toxicity (single exposure), Category 3  
 Specific Target Organ Toxicity (repeated exposure), Category 1  
 Aspiration Toxicity, Category 1



**GHS Signal Word:** **Danger**

**GHS Hazard Phrases:** H220: Extremely flammable gas.  
 H225: Highly flammable liquid and vapor.  
 H280: Containers gas under pressure; may explode if heated.  
 H304: May be fatal if swallowed and enters airways.  
 H315: Causes skin irritation.  
 H317: May cause an allergic skin reaction.  
 H319: Causes serious eye irritation.  
 H335: May cause respiratory irritation.  
 H341: Suspected of causing genetic defects.  
 H361: Suspected of damaging fertility or the unborn child {}.  
 H372: Causes damage to organs {} through prolonged or repeated exposure.  
 HUS1: May displace oxygen and cause rapid suffocation.

**GHS Precautionary Phrases:** P201: Obtain special instructions before use.  
 P202: Do not handle until all safety precautions have been read and understood.  
 P210: Keep away from protective gloves/protective clothing/eye protection/face protection. - No smoking.  
 P233: Keep container tightly closed.  
 P240: Ground/bond container and receiving equipment.  
 P241: Use explosion-proof electrical/ventilating/lighting/equipment.  
 P242: Use only non-sparking tools.

## Bulldog Adhesion Promoter Aerosol Formula

Printed: 08/24/2023

Revision: 08/24/2023

Supersedes Revision: 08/21/2023

<b>GHS Response Phrases:</b>	<p>P243: Take precautionary measures against static discharge.</p> <p>P260: Do not breathe protective gloves/protective clothing/eye protection/face protection.</p> <p>P264: Wash protective gloves/protective clothing/eye protection/face protection thoroughly after handling.</p> <p>P270: Do not eat, drink or smoke when using this product.</p> <p>P271: Use only outdoors or in a well-ventilated area.</p> <p>P272: Contaminated work clothing should not be allowed out of the workplace.</p> <p>P280: Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P281: Use personal protective equipment as required.</p> <p>P235: Keep cool.</p> <p>P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.</p> <p>P302+352: IF ON SKIN: Wash with plenty of soap and water.</p> <p>P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.</p> <p>P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.</p> <p>P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P308+313: IF exposed or concerned: Get medical attention/advice.</p> <p>P312: Call a POISON CENTER or doctor/physician if you feel unwell.</p> <p>P314: Get medical attention/advice if you feel unwell.</p> <p>P321: Specific treatment see on the label.</p> <p>P331: Do NOT induce vomiting.</p> <p>P332+313: If skin irritation occurs, get medical advice/attention.</p> <p>P333+313: If skin irritation or rash occurs, seek medical advice/attention.</p> <p>P337+313: If eye irritation persists, get medical advice/attention.</p> <p>P362: Take off contaminated clothing and wash before re-use.</p> <p>P363: Wash contaminated clothing before reuse.</p> <p>P370+378: In case of fire, use to extinguish.</p> <p>P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely.</p> <p>P381: Eliminate all ignition sources if safe to do so.</p>
<b>GHS Storage and Disposal Phrases:</b>	<p>P403+233: Store container tightly closed in well-ventilated place.</p> <p>P405: Store locked up.</p> <p>P410+403: Protect from sunlight and store in well-ventilated place.</p> <p>P501: Dispose of contents/container according to local, state and federal regulations.</p>
<b>Potential Health Effects (Acute and Chronic):</b>	Listed above.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
115-10-6	Methyl ether {Dimethyl ether}	30.0 -60.0 %
108-88-3	Toluene {Benzene, Methyl-; Toluol}	10.0 -30.0 %
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	7.0 -13.0 %
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	5.0 -10.0 %
123-86-4	Butyl acetate {n-Butyl acetate. Acetic acid, Butyl ester}	5.0 -10.0 %
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	1.0 -5.0 %
1321-74-0	Divinyl benzene (Benzene, Diethenyl-)	1.0 -5.0 %
100-42-5	Styrene {Phenylethylene; Vinyl benzine; Styrol}	1.0 -5.0 %

## Bulldog Adhesion Promoter Aerosol Formula

Printed: 08/24/2023

Revision: 08/24/2023

Supersedes Revision: 08/21/2023

100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	1.0 -5.0 %
97-63-2	Ethyl methacrylate {2-Propenoic acie, 2-methyl-, ethyl ester}	0.1 -1.0 %

**Additional Chemical Information** Specific percentage of composition is being withheld as a trade secret.

## 4. FIRST AID MEASURES

<b>Emergency and First Aid Procedures:</b>	<p><b>INHALATION:</b> If user experiences breathing difficulty, move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.</p> <p><b>SKIN CONTACT:</b> Wash with soap and water. Get medical attention if irritation develops or persists.</p> <p><b>EYE CONTACT:</b> Immediately flush eyes with water for at least 15 minutes. Remove contact lenses if worn. Seek medical attention.</p> <p><b>INGESTION:</b> If swallowed, do NOT induce vomiting. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person.</p>
<b>Signs and Symptoms Of Exposure:</b>	Refer to Section 2.

## 5. FIRE FIGHTING MEASURES

<b>Flash Pt:</b>	42.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)
<b>Explosive Limits:</b>	LEL: N.D. UEL: N.D.
<b>Autoignition Pt:</b>	N.D.
<b>Suitable Extinguishing Media:</b>	Use carbon dioxide, dry powder, or foam.
<b>Fire Fighting Instructions:</b>	<p>As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.</p> <p>Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.</p>
<b>Flammable Properties and Hazards:</b>	Danger! Flammable! Keep away from heat, sparks, flame, and all other sources of ignition. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Beware of static electricity that may be generated by synthetic clothing and other sources. Vapors can travel to a source of ignition and flash back.
<b>Hazardous Combustion Products:</b>	Carbon monoxide and carbon dioxide. Irritating or toxic vapors and gases.

## Bulldog Adhesion Promoter Aerosol Formula

Printed: 08/24/2023

Revision: 08/24/2023

Supersedes Revision: 08/21/2023

## 6. ACCIDENTAL RELEASE MEASURES

**Steps To Be Taken In Case Material Is Released Or Spilled:**

Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways and bodies of water. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc.

Small spills: Take up with sand, earth or other noncombustible absorbent material and place in a container where applicable.

Large spills: Dike far ahead of spill for later disposal.

Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions To Be Taken in Handling:**

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.

Do not spread this product over large surface areas because fire and health safety risks will increase dramatically.

**Precautions To Be Taken in Storing:**

Store in a cool dry place. Avoid extreme high or low temperatures.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
108-88-3	Toluene {Benzene, Methyl-, Toluol}	ACGIH TLV	TLV: 50 ppm	
		OSHA PELs	PEL: 200 ppm STEL: 500 ppm/(10min) CEIL: 300 ppm	
		ACGIH TLV	TLV: 200 ppm STEL: 300 ppm	
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	OSHA PELs	PEL: 200 ppm	
		ACGIH TLV	TLV: 100 ppm STEL: 150 ppm	
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	OSHA PELs	PEL: 100 ppm	
		ACGIH TLV	TLV: 150 ppm STEL: 200 ppm	
123-86-4	Butyl acetate {n-Butyl acetate, Acetic acid, Butyl ester}	ACGIH TLV	TLV: 150 ppm STEL: 200 ppm	

## Bulldog Adhesion Promoter Aerosol Formula

Printed: 08/24/2023

Revision: 08/24/2023

Supersedes Revision: 08/21/2023

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
123-86-4	Butyl acetate {n-Butyl acetate. Acetic acid, Butyl ester} (continued)	OSHA PELs	PEL: 150 ppm	
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	ACGIH TLV	TLV: 20 ppm	
		OSHA PELs	PEL: 50 ppm	
1321-74-0	Divinyl benzene (Benzene, Diethenyl-)	ACGIH TLV	TLV: 10 ppm	
100-42-5	Styrene {Phenylethylene; Vinyl benzene; Styrol}	ACGIH TLV	TLV: 20 ppm STEL: 40 ppm	
		OSHA PELs	PEL: 100 ppm STEL: 600 ppm/(5min/3hr) CEIL: 200 ppm	
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	ACGIH TLV	TLV: 100 ppm STEL: 125 ppm	
		OSHA PELs	PEL: 100 ppm	
<b>Respiratory Equipment (Specify Type):</b>	For use in areas with inadequate ventilation or fresh air, wear a properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors.			
	For OSHA controlled work places and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding the appropriate TLV.			
	A dust mask does not provide protection against vapors.			
<b>Eye Protection:</b>	A faceshield or chemical splash goggles should be worn to prevent eye contact.			
<b>Protective Gloves:</b>	Wear gloves with as much resistance to the chemical ingredients as possible. Glove materials such as nitrile rubber may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.			
<b>Other Protective Clothing:</b>	Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.			
<b>Engineering Controls (Ventilation etc.):</b>	Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.			
	Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to fresh air.			
<b>Work/Hygienic/Maintenance Practices:</b>	Wash hands thoroughly after use and before eating, drinking, smoking, or using the restroom.			
	Do not eat, drink, or smoke in the work area.			

## Bulldog Adhesion Promoter Aerosol Formula

Printed: 08/24/2023

Revision: 08/24/2023

Supersedes Revision: 08/21/2023

Discard any clothing or other protective equipment that cannot be decontaminated.

Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical States:</b>	[ X ] Gas    [ X ] Liquid    [ ] Solid
<b>Appearance and Odor:</b>	Hazy, Light Yellow Odor threshold not determined
<b>pH:</b>	Not applicable
<b>Melting Point:</b>	- N.D.
<b>Boiling Point:</b>	- N.D.
<b>Flash Pt:</b>	42.00 F    Method Used:    Setaflash Closed Cup (Rapid Setaflash)
<b>Evaporation Rate:</b>	> 1 (BuAC=1)
<b>Flammability (solid, gas):</b>	
<b>Explosive Limits:</b>	LEL: N.D.            UEL: N.D.
<b>Vapor Pressure (vs. Air or mm Hg):</b>	N.D.
<b>Vapor Density (vs. Air = 1):</b>	> 1
<b>Specific Gravity (Water = 1):</b>	0.8943
<b>Density:</b>	7.441 LB/GL
<b>Solubility in Water:</b>	Insoluble
<b>Saturated Vapor Concentration:</b>	N.D.
<b>Octanol/Water Partition Coefficient:</b>	N.D.
<b>Percent Volatile:</b>	91.4 % by weight.
<b>Autoignition Pt:</b>	N.D.
<b>Decomposition Temperature:</b>	- N.D.
<b>Viscosity:</b>	N.D.
<b>a_fld_hdr[9]:</b>	N.D.: Not determined NP: Not applicable

Information with regard to primary physical hazard:

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Unstable [ ]    Stable [ X ]
<b>Conditions To Avoid - Instability:</b>	
<b>Incompatibility - Materials To Avoid:</b>	Incompatible with strong oxidizing agents, strong caustics, acids, strong bases, hydrogen peroxide, nitric acid, nitrates, sulfuric acid, amines, chemically active metals, salts, aldehydes, ammonia, and halogens.
<b>Hazardous Decomposition or Byproducts:</b>	Thermal decomposition may produce carbon monoxide, carbon dioxide, acrylic monomers, acrid smoke and fumes.

## Bulldog Adhesion Promoter Aerosol Formula

Printed: 08/24/2023

Revision: 08/24/2023

Supersedes Revision: 08/21/2023

Possibility of Hazardous Reactions: Will occur [ ] Will not occur [ X ]

Reactions:

Conditions To Avoid -

Hazardous Reactions:

**11. TOXICOLOGICAL INFORMATION**

**Toxicological Information:** Product has not been tested as a whole. Refer to section 2 for acute and chronic health effects.

CAS# 108-88-3:

Reproductive Effects:, TClO, Inhalation, Rat, 800.0 MG/M3, 6 H, female 14-20 day(s) after conception.

Result:

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

Effects on Newborn: Behavioral.

- Brazilian Journal of Medical and Biological Research., Vol/p/yr: 23,533, 1990

Standard Draize Test, Eyes, Species: Rabbit, 2.000 MG, 24 H, Severe.

Result:

Effects on Embryo or Fetus: Other effects to embryo.

Specific Developmental Abnormalities: Eye, ear.

- Prehled Prumyslove Toxikologie, Marhold, J., Organicke Latky, Prague Czechoslovakia, Vol/p/yr: -,29, 1986

CAS# 78-93-3:

Standard Draize Test, Eyes, Human, 350.0 PPM.

Result:

Behavioral: Anticonvulsant.

- Journal of Industrial Hygiene and Toxicology, Vol/p/yr: 25,282, 1943

CAS# 1330-20-7:

Acute toxicity, LC50, Inhalation, Rat, 5000. PPM, 4 H.

Result:

Behavioral: Muscle contraction or spasticity.

Lungs, Thorax, or Respiration: Other changes.

- Raw Material Data Handbook, Vol.1: Organic Solvents, 1974., National Assoc. of Printing Ink Research Institute, Francis McDonald Sinclair Memorial Labor, Lehigh Univ., Bethlehem, PA 18015, Vol/p/yr: 1,123, 1974

Standard Draize Test, Eyes, Species: Rabbit, 5.000 MG, 24 H, Severe.

Result:

Behavioral: General anesthetic.

Behavioral: Somnolence (general depressed activity).

Behavioral: Irritability.

- "Sbornik Vysledku Toxixologickeho Vysetreni Latek A Pripravku," , Institut Pro Vychovu Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho, Prumyclu Praha Czechoslovakia, Vol/p/yr: -,24, 1972

CAS# 111-76-2:

Acute toxicity, LC50, Inhalation, Rat, 450.0 PPM, 4 H.

Result:

## Bulldog Adhesion Promoter Aerosol Formula

Printed: 08/24/2023

Revision: 08/24/2023

Supersedes Revision: 08/21/2023

Behavioral: Ataxia.

Nutritional and Gross Metabolic: Weight loss or decreased weight gain.

- Toxicology and Applied Pharmacology, Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 68,405, 1983

Acute toxicity, LD50, Skin, Species: Rabbit, 220.0 MG/KG.

Result:

Effects on Embryo or Fetus: Extra embryonic structures (e.g., placenta, umbilical cord).

Effects on Embryo or Fetus: Other effects to embryo.

Specific Developmental Abnormalities: Musculoskeletal system.

- Dow Chemical Company Reports., Dow Chemical USA, Health and Environment Research, Toxicology Research Lab, Midland, MI 48640, Vol/p/yr: MSD-46,

Acute toxicity, LD50, Oral, Rat, 250.0 mg/kg.

Result:

Lungs, Thorax, or Respiration: Changes in pulmonary vascular resistance.

Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, Severe.

Result:

Effects on Newborn: Apgar score (human only).

Effects on Newborn: Other neonatal measures or effects.

Effects on Newborn: Drug dependency.

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS# 100-41-4:

Tumorigenic Effects:, TLo, Inhalation, Rat, 750.0 ppm.

Result:

Tumorigenic: Carcinogenic by RTECS criteria.

Kidney, Ureter, Bladder: Tumors.

Standard Draize Test, Eyes, Species: Rabbit, 500.0 MG, Severe.

Result:

Effects on Fertility: Post-implantation mortality (e.g., dead and/or resorbed implants per total number of implants).

Effects on Fertility: Litter size (e.g.; # fetuses per litter; measured before birth).

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

**Carcinogenicity/Other Information:**

ACGIH A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans

ACGIH A4 - Not Classifiable as a Human Carcinogen.

IARC 2B - Possibly Carcinogenic to Humans

IARC 3: Not Classifiable as to Carcinogenicity in Humans.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
115-10-6	Methyl ether {Dimethyl ether}				
108-88-3	Toluene {Benzene, Methyl-, Toluol}		3	A4	
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}				



## Bulldog Adhesion Promoter Aerosol Formula

Printed: 08/24/2023

Revision: 08/24/2023

Supersedes Revision: 08/21/2023

1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}		3	A4
123-86-4	Butyl acetate {n-Butyl acetate. Acetic acid, Butyl ester}			
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}		3	A3
1321-74-0	Divinyl benzene (Benzene, Diethenyl-)			
100-42-5	Styrene {Phenylethylene; Vinyl benzine; Styrol}	Possible	2B	A4
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}		2B	A3
97-63-2	Ethyl methacrylate {2-Propenoic acie, 2-methyl-, ethyl ester}			

## 12. ECOLOGICAL INFORMATION

**General Ecological Information:** Product has not been tested as a whole.

## 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Dispose of in accordance with all applicable local, state, and federal regulations.

## 14. TRANSPORT INFORMATION

### LAND TRANSPORT (US DOT):

**DOT Proper Shipping Name:** Aerosols, [flammable, (each not exceeding 1 L capacity)]

**DOT Hazard Class:** 2.1 FLAMMABLE GAS

**UN/NA Number:** UN1950



**Additional Transport Information:** The shipper / supplier may be able to apply one of the following exceptions if allowed under 49 CFR Regulations: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49 CFR Hazmat Regulations. Please consult 49 CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

## 15. REGULATORY INFORMATION

### EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
115-10-6	Methyl ether {Dimethyl ether}	No	No	No
108-88-3	Toluene {Benzene, Methyl-; Toluol}	No	Yes NA	Yes
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	No	Yes NA	No
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	No	Yes NA	Yes
123-86-4	Butyl acetate {n-Butyl acetate. Acetic acid, Butyl ester}	No	Yes NA	No
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	No	No	Yes-Cat. N230
1321-74-0	Divinyl benzene (Benzene, Diethenyl-)	No	No	No
100-42-5	Styrene {Phenylethylene; Vinyl benzine; Styrol}	No	Yes NA	Yes
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	No	Yes NA	Yes
97-63-2	Ethyl methacrylate {2-Propenoic acie, 2-methyl-, ethyl ester}	No	Yes NA	No

## Bulldog Adhesion Promoter Aerosol Formula

Printed: 08/24/2023

Revision: 08/24/2023

Supersedes Revision: 08/21/2023

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
115-10-6	Methyl ether {Dimethyl ether}	TSCA: Inventory
108-88-3	Toluene {Benzene, Methyl-, Toluol}	CAA HAP,ODC: HAP: VHAP CWA NPDES TSCA: Inventory, 8A CAIR, 8C CA PROP.65: Yes: RDTox(F)
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	TSCA: Inventory
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	CAA HAP,ODC: HAP: VHAP CWA NPDES TSCA: Inventory
123-86-4	Butyl acetate {n-Butyl acetate. Acetic acid, Butyl ester}	CWA NPDES TSCA: Inventory
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	CAA HAP,ODC: Yes - Cat. TSCA: Inventory
1321-74-0	Divinyl benzene (Benzene, Diethenyl-)	TSCA: Inventory
100-42-5	Styrene {Phenylethylene; Vinyl benzene; Styrol}	CAA HAP,ODC: HAP: VHAP CWA NPDES TSCA: Inventory, 8A CAIR, 8C CA PROP.65: Yes: Canc.
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	CAA HAP,ODC: HAP: VHAP CWA NPDES TSCA: Inventory CA PROP.65: Yes: Canc.
97-63-2	Ethyl methacrylate {2-Propenoic acie, 2-methyl-, ethyl ester}	TSCA: Inventory

## 16. OTHER INFORMATION

**Revision Date:** 08/24/2023      **Previous revision:** 08/21/2023  
**Preparer Name:** W.M. Barr EHS Dept (901)775-0100

**Additional Information About This Product:**

**Company Policy or**

**Disclaimer:**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.